



OVERVIEW

The Triangle solution is widely used for different walls. The simple structure ensures quick installation and good strength. Professional packaging solution to save cost.

FEATURE

1. Universal design. Universal design for different walls.
2. Save installation time and labor cost. Simple triangle design saves the on-site installation time and labor cost.



SPECIFICATION

System Name	Wall Mounting System-Triangle System
Type	Wall
Tilt Angle	30°-35°
Wind Load	28m/s
Snow Load	0.58KN/m ²
Applicable Solar Module	Framed/Frameless
Panel Layout	Portrait/Landscape
Design Standard	BS EN1991, ASCE7-10, BS 6399, AS-NZS 1170, GB 50009-2012, MS 1553 AL-6005-T6 & SUS304
Material	1553 AL-6005-T6 & SUS304
Color	Sliver/Black
Warranty	10-year

CERTIFICATE



Description	1-Panel(H)	1-Panel(V)	2-Panel(V)
Rail 1250mm	0	2	0
Rail 2450mm	0	0	2
Bottom Beam	4	4	4
Beam	2	2	2
Pole	2	2	2
Bottom Beam Connector	2	2	2
Earthing Clip	4	2	2
Mid Clamp	0	0	2
End Clamp	4	4	4
Rail Clamp	0	4	4
Hexagon Socket Bolt	6	6	6
Grounding Lug	1	2	2
Expansion Bolts	8	8	8